

MODEL: PAC1811

TECHNICAL SPECIFICATIONS

COOLING CAPACIT	۲
VOLTAGE	
AMPS	
WATTS	
IN RUSH AMPS	
EER	

COMPRESSOR TYPE COMPRESSOR MOTOR COMPRESSOR RLA COMPRESSOR LRA

EVAPORATOR BLOWER EVAP CFM - HIGH EVAP MOTOR HP EVAP MOTOR AMPS EVAP MOTOR WATTS

CONDENSER BLOWER COND CFM COND MOTOR HP COND MOTOR AMPS COND MOTOR WATTS

POWER CORD PLUG TYPE CORD LENGTH

CONDENSATE REMOVAL SIZE

REFRIGERANT CHARGE

HEIGHT WITH CASTERS HEIGHT W/O CASTERS WIDTH DEPTH

NET WEIGHT SHIPPING WEIGHT SHIPPING VOLUME 16,800 BTUH 115 V, 60 Hz, Single Phase 14.1 A 1670 W 75 A 10.0

ROTARY 1-1/2 HP 12.3 A 63 A

CENTRIFUGAL 600 CFM 1/8 HP 1.8 A 210 W

CENTRIFUGAL 930 CFM 1/8 HP 2.1 A 280 W

14/3 5-20P, LCDI 10 FT

TANK 5 GALLON

R-410A 40 OZ.

45-3/4 in 40-1/2 in 24 in 30 in 260 lb.

285 lb. 28 cu. ft.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Cooling Capacity is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed

- A Time Delay fuses/circuit breakers are recommended
- \bigcirc EER is determined at high fan speed,

with condenser discharge air ducted into another area

CFM with free discharge

Amps & Watts at 115 Volts A

COOLING AMBIENT OPERATING RANGE 65° TO 105°



6228 OAKTON STREET MORTON GROVE, IL 60053 1-866-GET-AIRE Phone: (847) 583-0311 Fax: (847) 583-0312 WWW.OCEANAIRE-INC.COM OA-TS-PAC1811-02082017



WARRANTY

ALL OCEANAIRE PRODUCTS ARE COVERED BY THE OCEANAIRE LIMITED WARRANTY

1 YEAR ON THE FULL PRODUCT, PLUS 4 ADDITIONAL YEARS FOR THE COMPRESSOR (RESTRICTIONS APPLY)



NOT APPROVED FOR OUTDOOR USE





FEATURES

- OA 24 V CONTROL CIRCUIT
- OA NON-PROGRAMMABLE ELECTRONIC THERMOSTAT
- OA WASHABLE ELECTROSTATIC AIR FILTER
- OA REAR SWIVEL BALL BEARING CASTERS
- OA LOCKING FRONT CASTERS
- OA 2-SPEED FAN SWITCH
- OA CONDENSATE ALARM LIGHT
- OA LCDI POWER CORD
- **OA HIGH PRESSURE SAFETY SWITCH**

MODEL: PAC1811

OPTIONS* (FACTORY INSTALLED)

- OA HERESITE® COATED COIL (DIPPED)
- OA HOT GAS BYPASS FOR LOW AMBIENT APPLICATION
- OA REMOTE TEMPERATURE SENSOR
- OA REMOTE THERMOSTAT
- OA CONDENSER FAN CYCLE CONTROL

*OPTIONS MUST BE SPECIFIED AT TIME OF ORDER SOME OPTIONS ARE AVAILABLE IN NON-UL LISTED UNITS

